

ECO SMARTZ MOTORIZED MARSHALL STABILITY COMPRESSION 50kN

Standard: ASTM D1559, D5581, AASTHO T245, EN 12697-34, BS 598:107

Stability Compression

Newly invented bench mounting type machine, with rigid and compact design compare with previous model. By using DC motorised drive system to achieve more reliable and high accuracy result.



Technical Specifications :

Model Number	NL 2010 X / 006
Capacity	50 kN
Testing Speed	50.8 mm / min
Plunger Travel	60 mm
Vertical Clearance	730 mm
Horizontal Clearance	270 mm
Product Dimension	525 (L) x 445 (W) x 1150 (H) mm
Packing Dimension	670 (L) x 545 (W) x 1400 (H) mm
Approx. Product Weight	98 kg
Approx. Packing Weight	118 kg
Power	220 - 240 V, 2.5 Amp, 50 / 60 Hz, 1 ph, 370 W

Unit Consists Of :

Model Number	Accessories Description
NL 2010 X / 006 – P001	4" (100mm) Marshall Stability Mould c/w Flow Meter Attachment
NL 7023 X / 007	Proving Ring 30 kN
NL 2010 X / 006 – P002	Extended Plunger
NL 7020 X / 001	Dial Indicator 25 x 0.01 mm
NL 2010 X / 006 – P004	Handle (Manual Adjustment)

*1 Copy of Manual Instruction

Optional Accessories :

Model Number	Accessories Description
NL 2010 X / 006 – A001	6" (150 mm) Marshall Stability Mould c/w Flow Meter Attachment
NL 7023 X / 009	Proving Ring 50 kN
NL 2010 X / 004 – A004	Tensile Splitting Device (100, 150 & 160 mm)



NL 2010 X / 006 – A 001



NL 7023 X / 009



NL 2010 X / 004 – A 004