DIGIMATIC DRYING OVEN 125 LITRES

Standard: ASTM C127/C136 /D558/D698/D1559, EN 932-5/1097-5, BS 1377/1924



Drying Sample

The Digimatic Control Drying Oven exterior is a general purpose laboratory used such as soil, concrete, asphalt and aggregate. Internal frame made of stainless steel sheet and external casing coated with hard wearing paint & insulated with thick mineral wool. Heat generated by high precision digital controller & temperature range from RT + 10°C to 250°C. All capacity come with fan circulation blower. The oven come with glass viewing door surrounding casing is obtained with 50 mm thick fiber glass & steel shelves.

Technical Specifications :

Model Number	NL 1017 X / 008
Capacity	125 Litres
Voltage	220~240 V, 1 Ph, 50/60 Hz
Temp. Variation	RT+10-250 °C
Temp. Fluctuation	±5.0 °C
Temp. Resolution	0.1 °C
Ambient Temperature	+5-40 °C
Heating Power	2.3 KW, 10.5 A
Interior Dimension	500 (L) x 450 (W) x 550 (H) mm
Exterior Dimension	636 (L) x 580 (W) x 915 (H) mm
Packaging Dimension	730 (L) x 720 (W) x 1000 (H) mm
Load Per Shelve	25 kg / shelve (c/w 2nos shelves)
Gross / Net Weight	56 kg / 71 kg
Timing Range	1-9999 min

Optional Accessories :

Model Number	Accessories Description
NL 1017 X / 007 – P001	65 Litres Shelves with Bracket (Stainless Steel)
NL 1017 X / 008 – P001	125 Litres Shelves with Bracket (Stainless Steel)

* 1 Copy of Manual Instruction

Copyright 2026 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)