FIGURE GRAPE & ROCKCivil Engineering Testing Equipment

www.nl-test.com

DIGIMATIC DRYING OVEN 65 LITRES

Standard: ASTM C127/C136 /D558/D698/D1559, EN 932-5/1097-5, BS 1377/1924

Drying Sample

The Digimatic Control Drying Oven exterior is a general purpose laboratory used such as soil, concrete, asphalt and aggregate. Internal frame made of stainless steel sheet and external casing coated with hard wearing paint & insulated with thick mineral wool. Heat generated by high precision digital controller & temperature range from RT + 10°C to 250°C. All capacity come with fan circulation blower. The oven come with glass viewing door surrounding casing is obtained with 50 mm thick fiber glass & steel shelves.



Technical Specifications :

Model Number	NL 1017 X / 007
Capacity	65 Litres
Voltage	220 V, 1 ph, 50 / 60 Hz
Temp. Variation	RT+10-250 °C
Temp. Fluctuation	±5.0 °C
Temp. Resolution	0.1 ℃
Ambient Temperature	+5-40 °C
Heating Power	2.0 kW, 7 .5 A
Interior Dimension	400 (L) x 360 (W) x 450 (H) mm
Exterior Dimension	550 (L) x 550 (W) x 840 (H) mm
Packaging Dimension	610 (L) x 610 (W) x 905 (H) mm
Load Per Shelve	25 kg / shelve (c/w 2nos shelves)
Gross / Net Weight	47 / 61 kg
Timing Range	1-9999 min

^{* 1} Copy of Manual Instruction

Optional Accessories:

ĺ	Model Number	Parts Description
	NL 1017 X / 007 – P001	65 Litres Shelves with Bracket (Stainless Steel)

Copyright 2024 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)