## BITUMEN & ASPHALT

Technical Specifications :

**Civil Engineering Testing Equipment** 

www.nl-test.com

## LABORATORY CENTRIFUGE Standard: BS 598-102

## Centrifuge Extractor

This laboratory centrifuge is robust and compact in design and engineered to a high standard of reliability. It has the advantages of small volume, low noise, small temperature rise, high efficiency, safety and reliability.

| Model Number       | NL 2005 X / 001               |  |  |
|--------------------|-------------------------------|--|--|
| Maximum Speed      | 6000 rpm                      |  |  |
| Max. Capacity      | 5200 g                        |  |  |
| Timing Range       | 0 - 99 min                    |  |  |
| Power Supply       | AC 220 - 240 V ±10% 50 Hz 8 A |  |  |
| Approx. Weight     | 20 kg                         |  |  |
| Motor Power        | 480 W                         |  |  |
| Test Tube Capacity | 50ml x 6nos                   |  |  |
| Dimensions         | 340(L) x 400(W) x 270(H) mm   |  |  |

| Mod   | el Number          | Parts Description         | Qty   |
|-------|--------------------|---------------------------|-------|
| NL 20 | 005 X / 001 – P001 | Test Tubes c/w Steel Case | 6nos. |
|       |                    | (50ml)                    |       |



Copyright 2024 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 2(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)