



Panel



JOLTING APPARATUS (FULLY ENCLOSED VERSION)

Standard: EN 196-1, BS 3892, EN 130 679

Preparation of 40 x 40 x 160mm prisms

Similar to model NL 3006 X / 002, come with Fully Enclosed Soundproof Cabinet.

The apparatus used to compact cement mortar prism in the three gang mould. Made in galvanized chrome steel with quick locking device for sample. Structure in two parts, fixed and oscillating. Easily removable to check weight. Drop height 15 mm with a drop 60 drops per minute cycle. Control panel with main switch, main neon. Start / Stop button with digital selector, to select number of cycles which the machine automatically stop. Supply with emergency stop switched and built in feed hopper and quick clamp.

Technical Specifications :

Model Number	NL 3006 X / 003
Dimension (mm)	1150 (L) x 225 (W) x 360 (H)
Approx. Weight	39 kg
Power	220 - 240 V, 50 / 60 Hz, 1 ph

Unit Consists Of :

Model Number	Parts Description	Qty
NL 3006 X / 001 – P 002	Scraper (set of 2)	1set

*1 Copy of Manual Instruction

Optional Accessories :

Model Number	Accessories Description
NL 3006 X / 001 – A 001	Three Gang Mould For Prisms 40 x 40 x 160mm
NL 5001 X / 001 – A 023	Strength Edge: 300x30x3mm