

FLOW TABLE APPARATUS (ASTM)

Standard: ASTM C230

Consistency, Flow, Workable Life & Water Vapour
Permeability of Mortars

Used in making flow tests for consistency of mortars in tests of hydraulic cement and building limes.

Offering ASTM specification with an option either manual operated or motorized operated.

The top plate made of high quality brass with smooth plane surface finishing. Supplied with mold and tamper.



NL 3016 X / 001



NL 3016 X / 001 - A 001



NL 3016 X / 001 - A002

Technical Specifications :

Model Number	NL 3016 X / 002	NL 3016 X / 001
Type	Hand Operated	Motorized Operated
Dimension (mm)	310 (L) x 255 (W) x 245 (H)	
Diameter of Table	Ø254 mm (brass)	
Height of Drop	12.7 mm	
Flow Table Weight	4.08 kg	
Approx. Weight	14.6 kg	
Power	-	220 V, 1 ph, 50 / 60 Hz

Set Consists Of :

Model Number	NL 3016 X / 002	NL 3016 X / 001
NL 3016 X / 001 - P 001	Flow Mould - Top Ø69.9 Bottom Ø101.6, 50.8 mm (H)	
NL ADC 100	-	Armortron Controller
NL 3016 X / 001 - P 004	Hardwood Tamper (12 x 25 x 150 mm)	

*1 Copy Manual Instruction

Optional Accessories :

Model Number	Accessories Description
NL 3016 X / 001 - A 001	Flow Caliper (ASTM)
NL 3016 X / 001 - A 002	Acrylic Retainer Disc



NL 3016 X / 002