

DIGIMATIC AIR ENTRAINMENT METER(1 LITRE)

Standard: ASTM C185, AASHTO T152, BS 1881, EN 12350-7

Air Content of Cement Mortar

This product used to determine the air content in cement mortar, cement paste and lime mortar. Connected to a digital gauge directly collect air entrainment in percentage, with range of 0 - 20%. It is cast aluminium built, the test pot and upper part are air-tight sealed.

Technical Specifications :

Model Number	NL 3036 X / 004
Capacity	1 Litre
Air Content Range	0 - 20 %
Pressure Range	100 kPa
Gauge Battery Usage	8 hours
Reading Resolution	0.01% and 0.01 kPa
Approx Weight	3.6 kg (Air Meter Kit)
Case Dimension (mm)	260(L) x 260(W) x 460(H)

Unit Consist Of:

Model Number	Parts Description	Qty
NL 3036 X / 004 - P001	Strike Off Bar	1no.
NL 3036 X / 004 - P002	Calibration Tube (Brass)	1no.
NL 3036 X / 004 - P003	Charger Cable	1no.
NL 3036 X / 004 - P004	Carrying Case	1no.
NL 4023 X / 004 - P005	Rubber Teats	1no.
NL 7000 G / 003	Glass Measuring Cylinder 50ml	1no.

*1 Copy of Manual Instruction



Copyright 2023 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)