

CORING MACHINE 5.5HP 4-STROKE PETROL ENGINE

Standard: EN 12390-4, ASTM C39, AASHTO T22

Drilling & Coring

Portable petrol engine coring unit. Special cast aluminium main frame solid vertical movement pole and strong steel base with 4" Delrin wheels. Built-in water swivel for cooling the diamond bit.

***Supplied WITHOUT core bit set.**

Technical Specifications :

Model Number	NL 4006 P / 002
Max. Core Bit	6" or 150 mm (up to 500 mm coring depth)
Engine	Briggs & Stratton, USA, Series 750, 5.5Hp (161cc)
Gross Torque	9.8Nm @ 2,600 rpm
Materials Processed	Concrete, Asphalt, Rock
Cooling System	Integrated Water-Cooling System
Spindle Thread	1-1/4" UNC
Product Dimension	770 (L) x 450 (W) x 1110 (H) mm
Packing Dimension	870 (L) x 550 (W) x 1300 (H) mm
Approx. Product Weight	87 kg
Approx. Packing Weight	97 kg

*1 Copy of Manual Instruction

Unit Consists :

Model Number	Parts Description	Qty
NL 4006 P / 002 – P002	Strap Wrench & Spanner	1set
NL 4009 X / 009 – P004	1 1/4" x 3P Bit Adaptor	1no.

Optional Accessories :

Model Number	Parts Description	Qty
NL 7018 X Serial	Core Bit Set (Refer to NL 7018 X Group)	1pc
NL 4006 X / 002 – A001	Core Extractor	1set



Briggs & Stratton Series 750 5.5HP

Copyright 2025 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)