

www.nl-test.com

CORING MACHINE 9HP 4 STROKE ENGINE

Standard: EN 12390-4, ASTM C39, AASHTO T22

Drilling & Coring

Portable petrol engine coring unit. Special cast aluminium main frame solid vertical movement pole and strong steel base with 4" Delrin wheels. Built-in water swivel for cooling the diamond bit.

*Supplied WITHOUT core bit set.

Technical Specifications:

| Model Number | NL 4006 X / 003 |
|------------------------|----------------------------------|
| Max. Core Bit | 8" or 200 mm |
| Engine | Honda Petrol Engine GX270 (9 Hp) |
| Spindle Thread | 1-1/4" UNC |
| Product Dimension | 900 (L) x 780 (W) x 1200 (H) mm |
| Packing Dimension | 1050 (L) x 930 (W) x 1350 (H) mm |
| Approx. Product Weight | 273 kg |
| Approx. Packing Weight | 280 kg |

^{*1} Copy of Manual Instruction

Unit Consists:

| Model Number | Parts Description | Qty |
|------------------------|------------------------|------|
| NL 4006 P / 002 – P002 | Strap Wrench & Spanner | 1set |
| NL 4009 X / 009 – P004 | 11/4" x 3P Bit Adaptor | 1no. |

Optional Accessories:

| Model Number | Parts Description | Qty |
|------------------------|-----------------------------------------|------|
| NL 7018 X Serial | Core Bit Set (Refer to NL 7018 X Group) | 1pc |
| NL 4006 X / 002 – A001 | Core Extractor | 1set |





Copyright 2025 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 1 (All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)