



Profometer Rebar Diameter & Cover Meter

PM8000

the advanced concrete cover meter, from concrete rebar detection to line scanning. Precise concrete rebar cover measurements and diameter estimation with great clarity.



Precision

Sophisticated data interpolation and intelligent auto-mode eliminate error margin



Ergonomics

Compact, ultra light-weight and fully wireless - designed for use in rough environments



Productivity

Instant availability of data analytics and visualization in the field, data synchronization and collaboration



Profometer App

Tech Specs

Measurement Modes	Area Scan*
	Multiline Scan*
	Line Scan
	Spot data import
Review Modes	Area scan view*
	Multiline scan view*
	Line scan view
	Signal strength view
	Statistics
Advanced visualization	Heat Map*
	Augmented Reality (AR)*
	DBV (Deutscher Beton- und Bautechnik-Verein) advanced statistics*
Image processing	Auto rebar spacing first rebar layer*
	Neighbouring rebar correction first layer
	Neighbouring rebar correction second layer
	Align rebar positions*
Display settings	Concrete cover threshold slider with colour palette
On-site annotations	Markers
	photos
	geolocation
	voice notes
Reporting	Workspace integration
	Share via URL
	Automatic Logbook
	Raw data export
	Instant report generation
Export formats	JPG (Screenshot)
	PNG
	CSV
	HTML
Display Unit Specs**:	Latest Apple® iPad recommended (iPad with iOS 13.0 and higher)
	Screen size: From 7.9" to 12.9"
	Resolution: Up to 2732-by-2048
	Memory: Up to 2TB
	Weight: Down to 301 g / 10.6 oz
	Camera: Up to 12MP Wide and 10MP Ultra Wide
	Optional: USB-C, 5G, Face ID
Display Unit Sensors**:	LiDAR Scanner (optional)
	Three-axis gyro
	Accelerometer
	Ambient light sensor
	Barometer
	Built-in GPS/GNSS

* PM8000 Pro only

** Depending on iPad model iPad is a trademark of Apple Inc.; iOS is a registered trademark of Cisco in the US and is used by Apple under license



Instrument

Tech Specs

Technology	Eddy-current
Connection	Wireless
Cover Measuring depth	Up to 185 mm / 7.3 in
Cover Measuring Accuracy	+/- 1 mm / 0.04 in to 4 mm / 0.16 in depending on depth
Rebar Diameter Measuring Depth	up to 63 mm / 2.5 in
Rebar Diameter Measuring Accuracy	+/- 1 rebar size (Possible under optimal conditions. Please refer to the manual)
Encoder Accuracy	+/- 0.5mm / 0.02 in + 0.5% of measured length
Max Scanning Speed	0.5m/s - 1.7 ft / s
Max Line Scan Distance	1km / 0.6 miles
Display	High-contrast OLED screen
Dimensions	250 x 130 x 45 mm / 9.8 x 5.1 x 1.8 in (with cart)
	190 x 75 x 45 mm / 7.5 x 3.0 x 1.8 in (without cart)
Weight	690 g / 1.5 lb (with cart)
	300 g / 0.7 lb (without cart)
Battery	2 x AA (NiMH) rechargeable or non rechargeable
	Removable
	Flight-safe
	8 hours autonomy
	USB-C power bank (not included)



Our Accessories

Image	PartNumber	Description
	39222010	Telescopic rod kit for Profometer PM8000 instruments including the universal tablet holder UTH100
	79330345	Chest harness kit for hands free operation of all iPad app based instruments: GP8000, GP8100, GP8800, PD8050, PM8000, PI8000...

Standards & Guidelines	Description
BS 1881, Part 204	
DGZfP B2	
DIN 1045	
SIA 262-1	
SN 505262	
SS 78-B4	
DBV Guidelines	

Authorized Distributor



NL SCIENTIFIC INSTRUMENTS SDN. BHD. (881121-P)
No. 16, Lorong Sungai Puloh 1A/KU6,
Taman Teknologi Gemilang,
Kawasan Perindustrian Sungai Puloh,
42100 Klang, Selangor, Malaysia.

Email
sales@nl-test.com

Hotline
+603-3884 6088

Website
www.nl-test.com