AUGER POWER HEAD

Drilling Apparatus

Designed to drill small holes in every sector mounts an Emak 2-stroke engine with chrome cylinder and forged-steel drive shaft and connecting rod. The engine controls are grouped together on just one hand making them the ideal solution for single man.
Auger Head NEED TO ORDER SEPARATELY.



Technical Specifications :

Model Number	NL 5013 X / 002
Drill	
Reduction Ratio	40 : 1
Punte-bits	Ø10 cm , Ø15 cm, Ø20 cm
Reduction Gearbox with Grease	Yes
Engine	
Type	Air-cooled Two Cycle Engine
Alternate Code	1E44F-2A
Power	1.4KW / 6500 r/min
Idle Speed	3000 ± 200r
Clutch Speed	4000 ± 300r
High Speed	8500 ± 300r
Total Displacement	51.7 CC
Way of Ignition	Electric Ignition (CDI)
Ignition System	Transistor Magneto
Form of Carburettor	Diaphragm
Fuel Applicable	Gasoline
Tank Capacity	1.2L



Set Consists Of :

Model Number	Description	Qty
NL 5013 X / 001 – P001	Auger Drill	1set

Optional Accessories :

Model Number	Description
NL 5013 X / 001 – A002	100mm Dia. x 800 mm lg. Auger Head
NL 5013 X / 001 – A003	150mm Dia. x 800 mm lg. Auger Head
NL 5013 X / 001 – A004	200mm Dia. x 800 mm lg. Auger Head
NL 5013 X / 002 – A001	Extension Rod 300mm lg. (Max. 900 mm extension or 3 rods)

Copyright 2026 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 4(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)